

Vacuum bench B3 on base with wheels spraying system S4 and tank CO assembled and installed

Item I348R

The machine is composed by:-
Vacuum bench placed on base with wheels with adjustable height for an easy displacement inside the factory and equipped with a silent and powerful engine to contain even more the nebulized adhesive. -Spray gun G6 with ergonomic handle which makes it an efficacious and precise alternative to brush. The spray gun can perform a jet from a minimum of 3 mm up to a maximum cone-shaped jet of 50 mm. -Stainless steel tank 10 lt. capacity treated with non-stick Teflon.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty or when the vacuum bench is not intaking properly. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

Technical Data:

29/07/2022

Capaciy m3/h: 800	Volt: 230	Pressure head: 70	Air (lt/min):	Bar: 0
Decibel: 63.3	Watt: 36	Hertz: 50	Ampere: 0.31/0.36	Average Consumption:
Gross Weight: 45,73	Tare (kg): 0	Lenght (mt): 0,46	Height (mt): 0,64	Volume (m3): 0,23584
Net Weight: 45,73		Width: 0,6	Working surface (cm): 60 x 37	