

### Vacuum bench B9 spraying system S8 and tank C0

**Item 1988**

The machine is composed by: - Vacuum bench created to absorb even more the nebulized adhesive, equipped with two silent and powerful engines. -Spray gun G6 designed for both precise and large areas bonding. In particular it is possible to spray the glue from a minimum of 3 mm up to a maximum of 50 mm. -Stainless steel tank 10 lt. capacity, treated with non-stick Teflon.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty or when the vacuum bench is not intaking properly. To speed up the working process it is possible to use some nets in order to reduce the idle time due to loading and unloading the pieces on the working area. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

**Technical Data:**

29/07/2022

Capaciy m3/h: 2400 x2	Volt: 230	Pressure head: 270	Air (lt/min):	Bar: 0
Decibel: 72/67	Watt: 245 x2	Hertz: 50/60	Ampere: 2,6	Average Consumption:
Gross Weight: 147,65	Tare (kg): 20,65	Lenght (mt): 0,7	Height (mt): 1,7	Volume (m3): 2,358
Net Weight: 127		Width: 1,76	<b>Working surface (cm): 174 x 70</b>	